

AMERICAN NATIONAL RUBBER

The leader in closed cell rubber manufacturing since 1957

REBONDED RUBBER - 3000-R

Flexible Rebonded Rubber Joint Material



American National Rubber has been the leader of closed cell rubber manufacturing in U.S.A. since 1957. ANR 3000-R Rebonded Rubber is formed from granulated high-quality ANR closed cell rubber that is securely bonded together. It is highly resilient, and will compress with little extrusion, and recover 90% of its original thickness. Rebonded Rubber is comprised of 97% ANR post-industrial recycled content and is made in the USA.

ANR 3000-R Rebonded Rubber is a very useful and is an accepted form of expansion joint filler today. It is used in concrete structures to compensate for movement; therefore it can be utilized in residential or commercial applications such as in wastewater treatment plants, dam projects, aqueducts, tunnels and airport runways. Rebonded sponge rubber is a very resilient and flexible bonded rubber joint filler.

ANR 3000-R Rebonded Rubber should be installed as detailed in drawings. The material is positioned against the forms, at interrupting columns or objects or adjacent abutting structures before placing concrete. Rebonded Rubber is easily cut or trimmed on the jobsite, or it can be ordered to specific, pre-cut pieces.

ANR 3000-R Rebonded Rubber meets the following specifications:

Density 30 pcf. Minimum (lbs. /cubic ft.)
ASTM D-1752, Type I
AASHTO M 153-70, Type I
Federal Specification HH-F-341-F, Type II, Class A



Available in sheet sizes of 36" x 54" or precut at the factory to your exact specification requirements.

American National Rubber | dba ANR Partners Inc.

address: PO Box 877 | 626 Main Street | Ceredo WV 25507

toll free: 1-800-624-3410 | phone: 304-453-1311 | fax: 304-453-2347